ZEPCAM T3 LIVE MULTI DOCKING STATION

DATASHEET CODE: T3 - DS10



The ZEPCAM T3 Live Multi Docking Station is a plug and play solution for bodycam recharge and automatic video transfer to the server. Installation is straightforward, the solution is cost effective and easy to use.



Specifications	
Functionalities	Charging of ZEPCAM T3 Live bodycams Automatic transfer of recordings and data from bodycams to the server that runs ZEPCAM Manager software
Supported cameras	ZEPCAM T3 Live (T3-BC03)
Number of bays	10 bays for concurrent recharging and data offloading of a maximum of 10 bodycams
System setup	 Docking station connected to server via local network or internet connection: no pairing with server needed Docking station connected to external power supply: The external power supply is connected to a power socket
Security	End-to-end security between T3 Live bodycams and ZEPCAM Server: encrypted connections and data between bodycams and server
Dimensions	340 x 220 x 70 mm (height incl. bays)
Weight	1.5kg (without bodycams and wiring)
Ports	2x RJ45 Gigabit Ethernet Full Duplex 1000BASE-T DC Power Connector USB 3 connector
Power supply	External power supply with power cable Range 100 – 240Vac 50/60Hz
Power consumption idle	2 W
Power consumption max	80W
Operating conditions	0-40 °C Humidity 20-80% RH
Network	RJ45 Gigabit ethernet fixed or dynamic IP
Extra functionalities	 The possibility to daisy chain up to 10 docking stations. Only 1 ethernet connection needed to connect multiple docking stations to the server Magnets for easy and self-locating docking